

Building Scalable Cisco Internetworks (CCNP BSCI)

Table of Contents

Volume 1

Course Introduction

Describing Network Requirements

- Cisco Network Models
- Enterprise Composite Network Model
- Traffic Conditions in a Converged Network
- Cisco SONA Framework and IIN
- Routing and Routing Protocols

Configuring EIGRP

Introducing EIGRP

- EIGRP Capabilities and Attributes
- Underlying Processes and Technologies
- EIGRP Operation
 - Example: EIGRP Tables

EIGRP Metric

Calculating the EIGRP Metric

- Example: EIGRP Metric Calculation

Integrating the EIGRP and IGRP Routes

Implementing and Verifying EIGRP

- Configuring Basic EIGRP
 - Example: Configuring EIGRP for IP
- Using a Wildcard Mask in EIGRP
 - Example: Wildcard Mask in EIGRP
- Configuring the ip default-network Command
 - Example: ip default-network Command
- Verify EIGRP IP Routes
 - Example: EIGRP Configuration
 - Example: R2 EIGRP Configuration
- Verify EIGRP IP Operations

Configuring Advanced EIGRP Options

- Route Summarization
- Configuring Manual Route Summarization
 - Example: Summarizing EIGRP Routes
 - Example: Router C Routing Table
- Load Balancing Across Equal Paths
- Configuring Load Balancing Across Unequal-Cost Paths
 - Example: Variance
- EIGRP Bandwidth Use Across WAN Links
- Configuring EIGRP Bandwidth Use Across WAN Links
 - Example: WAN Configuration—Frame Relay Hub-and-Spoke Topology
 - Example: WAN Configuration—Hybrid Multipoint

Configuring EIGRP Authentication

- Router Authentication
- MD5 Authentication
- Configuring MD5 Authentication
 - Example: MD5 Authentication Configuration
 - Example: R1 Configuration for MD5 Authentication
 - Example: R2 Configuration for MD5 Authentication
 - Verifying MD5 Authentication

Troubleshooting MD5 Authentication

- Example: Successful MD5 Authentication

- Example: Troubleshooting MD5 Authentication Problems

Using EIGRP in an Enterprise Network

- Scalability in Large Networks
- EIGRP Queries
- EIGRP Stubs
 - Example: Limiting Updates and Queries: Using EIGRP Stub
 - Example: eigrp stub Parameters
- SIA Connections
- Preventing SIA Connections
- Graceful Shutdown

Configuring OSPF

Introducing the OSPF Protocol

- Link-State Routing Protocols
- OSPF Area Structure
- OSPF Adjacency Databases
- Calculating the OSPF Metric
 - Example: SPF Calculation
- Link-State Data Structures

OSPF Packet Types

- OSPF Packet Types
- Establishing OSPF Neighbor Adjacencies
- Exchanging and Synchronizing LSDBs
- Maintaining Network Routes
- Maintaining Link-State Sequence Numbers
 - Example: LSA Sequence Numbers and Maximum Age
- Verifying Packet Flow
 - Example: debug ip ospf packet

Configuring OSPF Routing

- Configuring Basic Single-Area and Multiarea OSPF
 - Example: Configuring OSPF on Internal Routers of a Single Area
 - Example: Configuring OSPF for Multiple Areas
- Configuring a Router ID
- Verifying the OSPF Router ID
- Verifying OSPF Operation
 - Example: The show ip route ospf Command
 - Example: The show ip ospf interface Command
 - Example: The show ip ospf neighbor Command

OSPF Network Types

- Introducing OSPF Network Types
- Adjacency Behavior for a Point-to-Point Link
- Adjacency Behavior for a Broadcast Network Link
- Selecting the DR and BDR
- Adjacency Behavior for an NBMA Network
- OSPF over Frame Relay Configuration Options
 - Example: Sample Configuration of a Router Using OSPF Broadcast Mode
- OSPF over Frame Relay NBMA Configuration
 - Example: neighbor Command
 - Example: show ip ospf neighbor Command
- OSPF over Frame Relay Point-to-Multipoint Configuration
 - Example: Point-to-Multipoint Configuration
- Using Subinterfaces in OSPF over Frame Relay Configuration
 - Example: Point-to-Point Subinterface
 - Example: Multipoint Subinterface
- Tracking OSPF Adjacencies
 - Example: debug Output for Point-to-Point Mode
 - Example: debug ip ospf adj Output for Broadcast Mode

Link-State Advertisements

- OSPF Router Types
 - Example: OSPF Hierarchical Routing
- OSPF Virtual Links
 - Example: OSPF Virtual Link Configuration
 - Example: show ip ospf virtual-links Command
- OSPF LSA Types
 - Type 1
 - Type 2
 - Types 3 and 4
 - Type 5
 - Type 6
 - Type 7
 - Type 8
 - Types 9, 10, and 11
 - Interpreting the OSPF LSDB and Routing Table
 - Example: Interpreting the OSPF Database
- Configuring OSPF LSDB Overload Protection
- Changing the Cost Metric

Configuring OSPF Special Area Types

- Configuring OSPF Area Types
- Configuring Stub Areas
 - Example: OSPF Stub Area Configuration
- Configuring Totally Stubby Areas
 - Example: Totally Stubby Configuration
- Interpreting Routing Tables
 - Example: Routing Table in a Standard Area
 - Example: Routing Table in a Stub Area
 - Example: Routing Table in a Stub Area with Summarization
 - Example: Routing Table in a Totally Stubby Area 3
- Configuring NSSAs
 - Example: NSSA Configuration
 - Example: NSSA Totally Stubby Configuration
 - Verifying All Stub Area Types

Configuring OSPF Authentication

- Types of Authentication
- Configuring Simple Password Authentication
 - Example: Simple Password Authentication Configuration
 - Example: R2 Configuration for Simple Password Authentication
 - Verifying Simple Password Authentication
- Configuring MD5 Authentication
 - Example: MD5 Authentication Configuration
 - Example: R2 Configuration for MD5 Authentication
 - Verifying MD5 Authentication
- Troubleshooting Simple Password Authentication
 - Example: Successful Simple Password Authentication
 - Example: Troubleshooting Simple Password Authentication Problems
- Troubleshooting MD5 Authentication
 - Example: Successful MD5 Authentication
 - Example: Troubleshooting MD5 Authentication Problems

Introducing IS-IS and Integrated IS-IS Routing

- IS-IS Routing
- Integrated IS-IS Routing
- Principles and Issues of Integrated IS-IS Design
- The ES-IS Protocol
- OSI Routing Levels
 - Level 0 Routing
 - IS-IS Level 1 Routing

- IS-IS Level 2 Routing
- Level 3 Routing
- Comparing IS-IS to OSPF

Performing IS-IS Routing Operations

- NSAP Addresses
- NET Addresses
- IS-IS Routing Levels
- Intra-Area and Interarea Addressing and Routing
 - Example: Identifying Systems—OSI Addressing in Networks
 - Example: OSI Area Routing
- IS-IS PDUs
- Link-State Packets
 - Example: LSP TLV Examples
- Implementing IS-IS in NBMA Networks
- Implementing IS-IS in Broadcast Networks
- LSP and IIH Levels
 - Level 1 and Level 2 LSP
 - Level 1 and Level 2 IIH
 - Example: Comparing Broadcast and Point-to-Point Topologies
- LSDB Synchronization
 - Example: LSDB Synchronization—LAN
 - Example: LSDB Synchronization: Point-to-Point
 - Example: WAN Adjacencies

Configuring Basic Integrated IS-IS

- Integrated IS-IS in a CLNS Environment
- Configuring Integrated IS-IS
 - Example: Simple Integrated IS-IS Configuration
- Optimizing IS-IS
 - Example: Tuning IS-IS Configuration
- Configuring Route Summarization in IS-IS
- Verifying IS-IS Configuration
 - Example: Is Integrated IS-IS Running?
- Verifying CLNS IS-IS Structures
 - Example: OSI Intra-Area and Interarea Routing

Volume 2

Operating a Network Using Multiple IP Routing Protocols

- Using Multiple IP Routing Protocols
- Defining Route Redistribution
- Using Seed Metrics
 - Seed Metrics Example
- Default Seed Metrics Example

Configuring and Verifying Route Redistribution

- Configuring Redistribution
 - Example: Redistribution Supports All Protocols
- Redistributing Routes into RIP
 - Example: Configuring Redistribution into RIP
 - Example: Redistributing into RIP
- Redistributing Routes into OSPF
 - Example: Configuring Redistribution into OSPF
 - Example: Redistributing into OSPF
- Redistributing Routes into EIGRP
 - Example: Configuring Redistribution into EIGRP
 - Example: Redistributing into EIGRP
- Redistributing Routes into IS-IS
 - Example: Configuring Redistribution into IS-IS
 - Example: Redistributing into IS-IS
- Verifying Route Redistribution

- Example: Before Redistribution
- Example: Routing Tables Before Redistribution
- Example: Configuring Redistribution
- Example: Routing Tables After Route Redistribution

Controlling Routing Update Traffic

- Configuring a Passive Interface
 - Example: Using the passive interface Command
- Configuring Route Filtering Using Distribute Lists
- Implementing the Distribute List
- Defining Route Maps
- Using route-map Commands
- Implementing Route Maps with Redistribution
 - Example: Route Maps and Redistribution Commands
- Defining Administrative Distance
 - Example: Administrative Distance
- Modifying Administrative Distance
- Defining the Impact of Administrative Distance Changes
 - Example: Redistribution Using Administrative Distance
 - Example: Configurations for the P3R1 and P3R2 Routers
 - Example: Routing Table After Redistribution
 - Example: Knowing Your Network

Implementing Advanced Cisco IOS Features: Configuring DHCP

- Describing the Purpose of DHCP
- Understanding the Function of DHCP
- Configuring DHCP
- Configuring the DHCP Client
- Explaining the IP Helper Address
- Configuring DHCP Relay Services

Implementing BGP

Explaining BGP Concepts and Terminology

- Using BGP in an Enterprise Network
- BGP Multihoming Options
 - Example: Default Routes from All Providers
 - Example: Default Routes from All Providers and Partial Table
 - Example: Full Routes from All Providers
- BGP Routing Between Autonomous Systems
 - BGP Is Used Between Autonomous Systems
 - AS Numbers
 - Comparison with IGPs
- Path-Vector Functionality
 - Example: BGP Routing Policies
- Features of BGP
- BGP Message Types

Explaining EBGP and IBGP

- BGP Neighbor Relationships
- Establishing EBGP Neighbor Relationships
- Establishing IBGP Neighbor Relationships
 - Example: Internal BGP
- IBGP on All Routers in Transit Path
 - IBGP in a Transit AS
 - IBGP in a Nontransit AS
 - Example: IBGP Partial Mesh
 - Example: IBGP Full Mesh
 - TCP and Full Mesh
 - Example: Routing Issues if BGP Is Not on in All Routers in Transit Path

Configuring Basic BGP Operations

- Initiate Basic BGP Configuration
- Activate a BGP Session
 - Example: BGP neighbor Command

- Shutting Down a BGP Neighbor
- BGP Configuration Considerations
 - Example: IBGP Peering Issue
 - Example: BGP Using Loopback Addresses
 - Example: ebgp-multihop Command
 - Example: Next-Hop Behavior
 - Example: next-hop-self Configuration
 - Example: Next Hop on a Multiaccess Network
 - Example: Using a Peer Group
 - Example: BGP network Command
 - Example: BGP Synchronization
 - Example: BGP Configuration
 - Example: BGP Configuration for Router B
- Identifying BGP Neighbor States
 - Example: show ip bgp neighbors Command
 - Example: BGP Active State Troubleshooting
 - Example: BGP Peering
- Authenticating in BGP
 - Example: BGP Neighbor Authentication
- Troubleshooting BGP
 - Example: show ip bgp Command Output
 - Example: show ip bgp rib-failure Command Output
 - Example: The debug ip bgp updates Command

Selecting a BGP Path

- Characteristics of BGP Attributes
- AS Path Attribute
 - Example: AS Path Attribute
- Next-Hop Attribute
 - Example: Next-Hop Attribute
- Origin Attribute
 - Example: Origin Attribute
- Local Preference Attribute
 - Example: Local Preference Attribute
- MED Attribute
 - Example: MED Attribute
- Weight Attribute
 - Example: Weight Attribute (Cisco Only)
- Determining the BGP Path Selection
- Selecting a BGP Path
 - Path Selection with Multihomed Connection

Using Route Maps to Manipulate Basic BGP Paths

- Setting Local Preference with Route Maps
 - Example: BGP Is Designed to Implement Policy Routing
 - Example: Local Preference Case Study
 - Example: BGP Table with Default Settings
 - Example: Route Map for Router A
- Setting the MED with Route Maps
 - Example: BGP Using Route Maps and the MED
- Implementing BGP in an Enterprise Network

Implementing Multicast

Explaining Multicast

- Explaining the Multicast Group
- IP Multicast Addresses

IGMP and Layer 2 Issues

- Introducing IGMPv2
- Introducing IGMPv3
- Multicast in Layer 2 Switching
- Cisco Group Management Protocol

- IGMP Snooping

Explaining Multicast Routing Protocols

- Protocols Used in Multicast
- Multicast Distribution Trees
- Introducing IP Multicast Routing
- Introducing PIM
- Describing PIM-DM
- Describing PIM-SM

Multicast Configuration and Verification

- Enabling PIM-SM and PIM Sparse-Dense Mode on an Interface
- Verifying IGMP Groups and IGMP Snooping
- Configure a Router to Be a Member of a Group or a Statically Connected Member

Implementing IPv6

- Explaining IPv6
- Describing IPv6 Features

Defining IPv6 Addressing

- Describing IPv6 Addressing Architecture
- Defining Address Representation
- IPv6 Address Types
 - Examples: Multiple ISPs and LANs with Multiple Routers

Implementing Dynamic IPv6 Addresses

- Defining Host Interface Addresses
 - Use of EUI-64 Format in IPv6 Addresses
 - IPv6 over Data Link Layers
 - EUI-64 to IPv6 Interface Identifier
- Explaining IPv6 Multicast
 - Addresses That Are Not Unique
- IPv6 Mobility
 - Mobile IPv6 Model

Using IPv6 with OSPF and Other Routing Protocols

- Describing IPv6 Routing
- OSPF and IPv6
 - How OSPF for IPv6 Works
- Comparing OSPF for IPv6 to OSPFv2
- LSA Types for IPv6
- LSAs
- Address Prefix
- Introducing OSPFv3 Configuration
- Configuring OSPFv3
 - Defining an OSPF IPv6 Area Range
- Verifying OSPFv3

Using IPv6 with IPv4

- Describing IPv6-to-IPv4 Transition Mechanisms
 - Other Tunneling and Transition Mechanisms
- Describing IPv6-over-IPv4 Tunneling Mechanisms and IPv4 Addresses in IPv6 Format
 - NAT-PT
 - BIA and BIS